



Float Pro Specifications

Document: v1 **Firmware:** v1.0.0 **Hardware:** v1.0.0

Applications	Tracking fermentation and temperature of: beer, wine, cider, mead etc.
Data Storage	Cloud data storage in your free My Brewbrain Personal account. Data is logged every 15 minutes.
Wireless connectivity	
Standard	Wi-Fi 802.11 b/g/n (2.4 GHz)
Security	WPA / WPA2 Personal
Encryption	WEP / TKIP / AES
Battery	
Lifetime when fully charged	4 months ¹
Charging ²	USB-C 5 V, 1.0 A, Wireless charging QI v1.2 compliant
Housing	
Materials ³	PET housing
	TPU compressible sealing ring
	Silicon lubricant for ring
Ingress protection	Waterproof (IP67) housing
Cleaning	Cleanable with conventional brewing cleaning agents
Temperature range	+2 °C to +60 °C (+36 °F to +140 °F)
Pressure range	+2 bar or 3 barg (+29 PSI or 43 PSIG)
Specific gravity⁴	
Range	0.970 - 1.150 SG
Accuracy	± 0.006 SG
Resolution	0.0001 SG
Temperature⁴	
Accuracy	± 0.25 °C (± 0.45 °F)
Resolution	0.0625 °C (0.1125 °F)
Weight	165 g (approximately 5.8 oz) ⁵
Size	183 x Ø 41 mm (approximately 7.2 x Ø 1.6")
Warranty	2 years
EAN	8 720844 085187

Note: These specifications serve as an indication and may be subject to change or corrections without prior notice

¹ Based on a measure interval of 15 minutes.

² Adapter and cable not included.

³ All housing materials are food-safe

⁴ Other units are configurable using the online platform (°P, °Oe, Brix, Baumé, KMW/Babo, °F, K)

⁵ The weight excludes packaging